



# DIGIPASS GO 6

## Time/event based strong authentication device.

For banks and other organizations who need to authenticate remote users, DIGIPASS GO 6 is a strong authentication device that boosts security while providing unmatched user acceptance. DIGIPASS GO 6 is waterproof, robust, affordable, easy to deploy and user friendly.

DIGIPASS® GO 6 is a 'one-button' authenticator, based on VASCO's proven DIGIPASS technology. Banks and other organizations can effectively combat internet fraud by replacing static or paper based password systems, using DIGIPASS GO 6.

As user acceptance is crucial for the success of security implementations, DIGIPASS GO 6 is extremely easy to use. The user simply presses one-button to generate a one-time password to remotely log into an application, website or network.

The elegant design of DIGIPASS GO 6 can be enhanced with your corporate logo, branding and custom colors. A transparent lens protects your logo and branding from normal wear and tear.

DIGIPASS GO 6 is fully interoperable with all members of the DIGIPASS family and works seamlessly with VASCO's VACMAN® or IDENTIKEY® authentication service products and over 50 different VASCO® partner applications.

With DIGIPASS and VACMAN/ IDENTIKEY, banks and other organizations can economically deploy a comprehensive, scalable, high performance two factor authentication solution for secure internet banking and network access.



#### **FEATURES**

- One-button operation for one-time password generation
- Strong two factor authentication, based upon possession of the DIGIPASS and (option) the knowledge of a password
- DIGIPASS time / event based algorithms
- Remote host authentication
- Customizable OTP length, OTP refresh frequency (for time based algorithms) and welcome message
- Easily customized with corporate logos, branding and company colors
- · Tamper evidence
- Supports VASCO's Multi OTP technology

#### **BENEFITS**

- · Compact, sleek design
- Sealed tightly to protect against dust and moisture; waterproof!
- Easy to use; consequently minimal training, low start-up costs and high user acceptance
- Easy to deploy
- Low total cost of ownership
- Long battery life resulting in reduced token replacement costs
- Designed for mass-deployment





#### **EASY TO DEPLOY**

The integration of DIGIPASS GO 6 into an existing network is simple and goes fast. Static passwords or existing TAN lists (pre-printed lists of TransAction Numbers) can instantly be replaced with the more secure DIGIPASS GO 6 dynamic password.

Once the unit has been initialized and provided to the user, costly user training is unnecessary.

#### **EASY TO USE**

With a single press of the button, DIGIPASS GO 6 displays a dynamic one-time password for each time a user remotely logs into an application, website or network. The user enters this one-time password in the login screen of the application.

An additional password, as a second factor of authentication, can also be applied to eliminate unauthorized use if the device is lost or stolen.

The portable DIGIPASS GO 6 can be carried on a key ring, worn around the neck or simply placed in a pocket or purse.

#### TECHNICAL SPECIFICATIONS

· Weight: 14 grams

• Dimensions: 9,8 x 25,9 x 62,7mm

• Display:high contrast 8-characters LCD

Keypad: one-button

· Real-time clock

Supported algorithms:

• DIGIPASS event and time based (DES, 3DES and AES)

• OATH event (HOTP) or time (TOTP) based (on demand)

• Battery: non-replaceable, lifetime expectancy 7 years

#### **CERTIFICATION AND COMPLIANCE**

CEITH ICATION AND COMILETANCE		
Short storage temperature	-10° C to 50° C; 90% RH non condensing	IEC 60068-2-78 (damp heat) IEC 60068-2-1 (cold)
Operating temperature	0° C to 45° C;85% RH non condensing	IEC 60068-2-78 (damp heat) IEC 60068-2-1 (cold)
Tampering	Tamper evidence	ISO 13491-1
Water resistance	Waterproof IPx7 (1 meter during 30 min)	ISO 60068-2-18 or IEC 60529
Vibration	10 to 75 Hz; 10 m/s2	IEC 60068-2-6
Drop	1 meter	IEC 60068-2-31
Emission		EN 55022
Immunity	4 kV contact discharges	EN 55024
	8 kV air discharges 3 V/m from 80 to 1000 MHz	
Compliant with European directives	<ul> <li>CE: 89/336/EEC or 2004/108/EC</li> <li>RoHS: 2002/95/EC</li> <li>WEEE: 2002/96/EC</li> </ul>	

## **About VASCO**

VASCO is a leading supplier of strong authentication and e-signature solutions and services specializing in Internet Security applications and transactions. VASCO has positioned itself as global software company for Internet Security and designs, develops, markets and supports patented DIGIPASS®, DIGIPASS PLUS®, VACMAN®, IDENTIKEY® and aXsGUARD® authentication products. VASCO's prime markets are the financial sector, enterprise security, e-commerce and e-government.

### www.vasco.com

BRUSSELS (Europe)

phone: +32.2.609.97.00 email: info-europe@vasco.com BOSTON (North America)

phone: +1.508.366.3400 email: info-usa@vasco.com

SYDNEY (Pacific)

phone: +61.2.8061.3700 email: info-australia@vasco.com SINGAPORE (Asia)

phone: +65.6323.0906 email: info-asia@vasco.com